

The Pacific Pipeline

The Monthly Newsletter of Pacific Pump and Power Rental • Sales • Service • Operations

June 2019
License# C-32223





Best Qualified Electro-Fusion Technicians in the State!

Pacific Pump & Power has really been ramping up our electro-fusion over the past few weeks! Conditions on our sites have required a significant number of electro-fusions to complement our butt-fusion work! These situations have included adding a flange adaptor to the end of a 32" pipe in tight space confines, an emergency repair and a large rework to an intricate piping system.

Similar to HDPE Butt-Fusion, electro-fusion, when done correctly per the ASTM standards, leaves the piping 105% the strength of the virgin piping with a 0% leak rate so we can rest assured that the fittings will be the strong points in the piping.

Pacific Pump & Power has three level 1, 2, and 3 electro-fusion certified technicians, meaning we have been certified by one of the most respected trainers in the country in all sizes of electro-fusion. Those of you familiar with us on butt-fusion know how precise our operators are at following the standards to ensure optimal results. You can now expect the same level of meticulousness on electro-fusion.

If you need assistance with fusion, compressed air, pumps, power, sewer bypass, pipe plugs, service or operations, please call us at 808-672-8198 or email Sales@PacificPumpandPower.com

Check us out on the web at www.PacificPumpandPower.com







The Pacific Pipeline

The Monthly Newsletter of Pacific Pump and Power

June 2019 License# C-32223

Rental • Sales • Service • Operations

Pump Type ahu Yard odwin Dri-Prime CD Series Pumps, High Volume,	Į.	
ndwin Dri-Prime CD Series Pumps High Volume		
and by the state of concertaining the volume,	46 AVAILABLE	DPC300 12" Diesel, up to 5000 gpm or up to 115' of head
edium Head, Large Solids-Handling Capabilities		DPC300 12" Electric, up to 4000 gpm or up to 115' of head DPC350" Disparation to 4000 gpm or up to 115' of head
		 CD2258"Diesel, up to 3100 gpm or up to 183' of head CD2258"Electric, up to 3100 gpm or up to 175' of head
		CD150M6" Diesel, up to 1700 gpm or up to 170 of head
		CD103M4"Diesel, up to 1000 gpm or up to 170' of head
		CD100M4" Diesel, up to 750 gpm, or up to 115' of head
odwin HL Series, High Head Pumps with Solids-	7 AVAILABLE	HL150M6"Diesel, up to 1450 gpm or up to 500' of head HL 90M 9"Diesel, up to 450 gpm or up to 900' of head
andling Capabilities	0.000	HL80M, 3" Diesel, up to 450 gpm or up to 325' of head
Godwin Heidra Hydraulic Submersibles	9 AVAILABLE	HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head US150V6" Diesel, up to 1600 gpm or up to 160' of head
		 HS150V6", Diesel, up to 1600 gpm or up to 160' of head HS100TD 4", Diesel, up to 800 gpm or up to 130' of head
		HS80HH3", Diesel, up to 420 gpm or up to 125' of head
Electric Submersibles	50 AVAILABLE	Godwin GSP600SV, 8", up to 3650 gpm or up to 82' of head
		Godwin GSP160HV, 6", up to 1200 gpm or up to 115' of head
		Godwin GSP55, 4", up to 550 gpm or up to 75' of head
		StancorSSS-100,2"Stainless,100gpmorupto60'ofhead
		• StancorSSS-75,2"Stainless,80gpmorupto40'ofhead
		Stancor SV-50, 2" Stainless, 80 gpm or up to 40' of head
		Stancor SV-1002" Stainless, 110 gpm or up to 50' of head Stancor SCP 200 2" Stainless 400 gpm or up to 55' of head
		 Stancor SSD-200, 3" Stainless, 180 gpmorup to 55' of head Stancor SEW-75, 2" Stainless, 95 gpm or up to 9' of head
		Stancor SEW-75, 2 Stainless, 95 gpm or up to 9 or nead Stancor SEW-100, 2" Stainless, 111 gpm or up to 35' of head
		Stancor SEW-100, 2 Stainless, 171 gpmorupto 52 of head Stancor SEW-200, 2" Stainless, 190 gpmorupto 52' of head
		• Flygt 2740 SS sludge series 244HT, 210 gpmor up to 80' of head
et-Prime Gas Trash Pumps	22 AVAILABLE	WT40X4"upto 430gpmorupto 92' of head
		GPP 50HX 2" Wet Prime Pressure GX160
		Godwin GTP50HX2" up to 185 gpm or up to 98' of head Godwin GTP90HX 2" up to 255 gpm or up to 98' of head
		 Godwin GTP80HX, 3" up to 355gpm or up to 90' of head Godwin GTP100HX, 4" up to 430 gpm or up to 92' of head
Versamatic Diaphragm Pumps	12 AVAILABLE	Versamatic Air Operated E3, 3", up to 260 gpm
	12 /11/112/15/22	Versamatic Air Operated E2, 2", up to 155 gpm
		Versamatic Air Operated E1, 1", up to 46 gpm
ydrostatic Test Pumps and Wheel Kit	1 AVAILABLE	Rice TR8H – Honda 13 HP, 389CC gasoline engine
ow Meter	1 AVAILABLE	12" M0300 Bolt on Saddle Flow Meter
Power Diesel Generator Sets	5 AVAILABLE	Godwin 26kW-R Series, Critically Silenced
		125kVA MultiQuip WhisperWatt
		Kubota 10kw Atlas Copco 25 kva
		Atlas Copco 330 kva
Gasoline Generator Sets	3 AVAILABLE	3000 & 2000 Watt, Portable Honda Quiet Model
Solino Contrator Cotto	O TIVITETIBLE	GeneracGenerator 10,000 Watt
odwin Portable Light Towers	3 AVAILABLE	GLT416, 4000 Watts, Coverage of 5-7 acres
oad Ramp Crossings	7 AVAILABLE	6", 8" and 12" Road Ramps Crossings
r Compressor	8 AVAILABLE	• 185cfm, 250cfm,400cfm, 750cfm
ydraulic Hoses	2,300 FEET	• ¼",½",¾" and 1" Hydraulic Hose with Couplers
eavy Duty Hoses	14,512 FEET	• 2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge
ary bury 110303	11,012121	Hose Available with Quick Disconnect Fittings
uer Light Weight, Quick Disconnect Pipe	5,795 FEET	4", 6", 8", and 12" Bauer Light Weight Quick Disconnect Pipe
	·	in 10' and 20' Lengths
Imp Accessories	4,000 IN STOCK	Bauerand Camlock Fittings from 2-12" Available A 10" DD 20 and 40" DD 20 5 LIDDE Ding.
OPE Pipes and Fittings	23,317 FEET	18"DR26and18"DR32.5HDPEPipe12"DR11 HDPEPipe
		□ 2", 3", 4", 6", 8", 10, 12", 14" 18", 24" HDPE Fittings
ımp Parts	1,600 IN STOCK	Common Wear Parts for all Pumps Already in Stock
pe Plugs	161 AVAILABLE	□ 4-8", 6", 8-12", 12-18", 18-24", 15-30", 24-36" and 24-42", 24-48", 84" with
,		Protective Sleeves and Poly-Lift Line Inflators
Elroy Fusion Machines	11 AVAILABLE	• T900 fuses 12-36" HDPE
		 T500 II fuses 6-20" HDPE, Rolling 618 fuses 6-18" HDPE, Rolling 28 fuses 2-8" HDPE PitBull 26 fuses 2-6" HDPE, 2LC fuses 1/2-2", Pitbull 14 fuses 1-4"
Elroy Parts	145 IN STOCK	Assorted parts and inserts
aui Yard		
uer Light Weight, Quick Disconnect Pipe	410 FEET	6"Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths
gg, La ion Liosofiilost i ipo	1	8" Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths
eavy Duty Hoses	120 FEET	6"Heavy Duty Suction Hoses Available with Quick Disconnect Fittings
ad Ramp Crossings	1 AVAILABLE	• 6"Roadramp crossing
asoline Generator Sets	1 AVAILABLE	2000 Watt, Portable Honda Quiet Model
Semile Contractor Social	TAVAILABLE	2000 Walt, 1 Ortable Florida Quiet Wodel













