Pump Troubleshooting and Service Guides

Pump Troubleshooting and Service Guides are put on our rental pumps for quick access to important information about running Godwin Dri-Prime Pump Systems. This information is available on our website, www.pacificpumpandpower.com, and we also have hard, plastic copies professionally printed. If you would like to purchase a set of the professionally printed copies, please contact us at (808) 672-8198.

A brief summary of the points on each card is below.

Safety Considerations

This instruction card, consisting of nine Do's and six Don'ts, provides guidelines for safe operation of Godwin Dri-Prime pump systems.

• Operating Instructions

This card includes the Pre-Startup Equipment Checklist, seven Equipment Startup Points, and three Equipment Shut-Down Points.

Simplified Troubleshooting

Should the Godwin Dri-Prime pump fail to prime, several simple checks can be made to isolate the problem. Tools required for trouble shooting include: crescent wrench and long handled screw driver or pry bar. This card includes six of the most common problems you might come across when operating Godwin Dri-Prime pump systems.

• Routine Servicing

Pumps, generators and light towers should be serviced every 250 hours of run time. We recommend that the date and total hours at servicing be written on the engine oil filter at each interval. This card details how to service the engine, pump end and air compressor and how to complete a vacuum pad test.









The Pacific Pipeline



The Monthly Newsletter of Pacific Pump and Power, Distributor of Godwin Pumps®


Rentals • Sales • Service

November 2008



61 Pumps, Generators and Light Plants Available for Rent or Purchase in Hawaii

Pump Type	Quantity	Pump Model and Description
	Available	
Godwin Dri-Prime CD Series Pumps,	32 AVAILABLE	•DPC300 12" Diesel, up to 5000 gpm or up to 115' of head
High Volume, Medium Head, Large Solids-Handling Capabilities		• DPC300 12" Electric, up to 4000 gpm or up to 115' of head
Large solids Figurialing Capabilities		•CD225M 8" Diesel, up to 3100 gpm or up to 183' of head
		◆CD225M 8" Electric, up to 3100 gpm or up to 175' of head ◆CD150M 6" Diesel, up to 1700 gpm or up to 160' of head
		•CD103M 4" Diesel, up to 1000 gpm or up to 170' of head
		•CD100M 4" Diesel, up to 750 gpm or up to 115' of head
		•CD80M 3" Diesel, up to 450 gpm or up to 93' of head
Godwin HL Series, High Head Pumps	7 AVAILABLE	●HL5M 6" Diesel, up to 1450 gpm or up to 500' of head
with Solids-Handling Capabilities		●HL80M, 3" Diesel, up to 450 gpm or up to 325' of head
Godwin Heidra Hydraulic Submersibles	2 AVAILABLE	 HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head HS100TD 4", Diesel, up to 800 gpm or up to 130' of head
Godwin Sub-Prime Electric Submersibles	7 AVAILABLE	●GSP600SV, 8", up to 3650 gpm or up to 82' of head
		●GSP160HV, 6", up to 1200 gpm or up to 115' of head
		•GSP55, 4", up to 550 gpm or up to 75' of head
Cody in Mat Dring Cod Track Drives	2 4) (4 4 5 5	• GSP10-115, 2", up to 90 gpm or up to 60' of head
Godwin Wet-Prime Gas Trash Pumps	2 AVAILABLE	●GTP80HX, 3"
Godwin Versamatic Diaphragm Pumps	7 AVAILABLE	• Versamatic Air Operated E3, 3", up to 260 gpm
		Versamatic Air Operated E2, 2", up to 155 gpm
Godwin Power Diesel Generator Sets	1 AVAILABLE	Versamatic Air Operated E4, 1 ½" x 1 ¼", up to 70 gpm
Gasoline Generator Sets	1 AVAILABLE	• 26kW-R Series, Critically Silenced
Godwin Portable Light Towers	3 AVAILABLE	• 3000 Watt, Portable Honda Model
Road Ramp Crossings	10 AVAILABLE	•GLT 416, 4000 Watts, Coverage of 5-7 acres
Hydraulic Hoses	800 FEET	• 4", 6", 8" and 12" Road Ramps Crossings
Heavy Duty Hoses	5920 FEET	 ¼", ½", ¾" and 1" Hydraulic Hose with Couplers 2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge
	37201 EE1	Hose Available with Quick Disconnect Fittings
Bauer Light Weight,	5780 FEET	•4", 6", 8", and 12" Bauer Light Weight Quick Disconnect
Quick Disconnect Pipe		Pipe in 10' and 20' Lengths
Pump Accessories	3700 IN STOCK	Bauer and Camlock Fittings from 2-12" Available
18" HDPE Pipe	1943 FEET	● 18" DR 26 and 18" DR 32½ HDPE Pipe
Pump Parts	950 IN STOCK	●Common Wear Parts for all Pumps Already in Stock
Cherne Pipe Plugs	12 AVAILABLE	•4-8", 8-12", 12-24", 15-30", 24-42", 24-36" with Sleeves and Inflators
Toyo Dredge Pumps	4 AVAILABLE	●DP-3 3" Submersible Electric, 132 gpm or up to 23' of head
		•DL-4 3" Submersible, Electric, 130 gpm or up to 40' of head
		●DL-1 2" Submersible Electric, 30 gpm or up to 27' of head







Pipe Plugs

For immediate assistance please contact: Patrick Baker, 721-0264, pbaker@pacificpumpandpower.com or Jeremy Leonard, 721-0127, jleonard@pacificpumpandpower.com