

Moving Poop in Kahala!!!



Pacific Pump and Power is running a sewer bypass for Michels Pipe Services so they can install Cured In Place Pipe (CIPP) in the existing 24" sewer line along Kahala Ave. CIPP is a process where a polyester felt liner is impregnated with polyester resin and inverted into a pipeline using either air or water. The liner is then heated for several hours which turn the liner into a solid pipe within a pipe! This rehabilitation work prevents groundwater intrusion into the sewer system and prevents sewer lines from collapsing. Michels has worked on numerous jobs lining major sewer lines throughout the Hawaiian Islands.





Pacific Pump and Power is providing Michels turnkey bypassing for this project along with operators on duty 24hr/day while the bypass runs. This bypass uses approximately 2,000 feet of 8" Bauer Quick-Disconnect steel galvanized piping with (2) 6" CD150M Critically Silenced pumps. The Critically Silenced pumps adhere to the 68db noise restriction in place while working on residential areas.



Michels is using 8" Road Ramps for all their road crossings.





The Pacific Pipeline



The Monthly Newsletter of Pacific Pump and Power, Distributor of Godwin Pumps[®]

Rental • Sales • Service

July 2010

80 Pumps, Generators and Light Plants and Dredges Available for Rent or Purchase in Hawaii

| D. 1999 T. 1999 | | Duran Madaland Description |
|--|-----------------------|--|
| Pump Type | Quantity Available | Pump Model and Description |
| Godwin Dri-Prime CD Series Pumps, High Volume, Medium Head, Large Solids-Handling Capabilities | 36 AVAILABLE | DPC300 12" Diesel, up to 5000 gpm or up to 115' of head DPC300 12" Electric, up to 4000 gpm or up to 115' of head CD225M 8" Diesel, up to 3100 gpm or up to 183' of head CD225M 8" Electric, up to 3100 gpm or up to 175' of head CD150M 6" Diesel, up to 1700 gpm or up to 160' of head CD103M 4" Diesel, up to 1000 gpm or up to 170' of head CD100M 4" Diesel, up to 750 gpm or up to 115' of head CD80M 3" Diesel, up to 450 gpm or up to 93' of head |
| Godwin HL Series, High Head Pumps with Solids-Handling Capabilities | 7 A VAILABLE | HL5M 6" Diesel, up to 1450 gpm or up to 500' of head HL80M, 3" Diesel, up to 450 gpm or up to 325' of head |
| Godwin Heidra Hydraulic Submersibles | 2 A VAILABLE | HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head HS100TD 4", Diesel, up to 800 gpm or up to 130' of head |
| Godwin Sub-Prime Electric Submersibles | 7 A VAILABLE | •GSP600SV, 8", up to 3650 gpm or up to 82' of head •GSP160HV, 6", up to 1200 gpm or up to 115' of head •GSP55, 4", up to 550 gpm or up to 75' of head |
| Godwin Wet-Prime Gas Trash Pumps | 3 A VAILABLE | •GTP80HX, 3" up to 355 gpm or up to 90' of head •GX340, 4" up to 425 gpm or up to 82' of head |
| Versamatic Diaphragm Pumps | 7 A VAILABLE | Versamatic Air Operated E3, 3", up to 260 gpm Versamatic Air Operated E2, 2", up to 155 gpm Versamatic Air Operated E4, 1½" x 1¼", up to 70 gpm |
| Toyo Dredge Pumps | 2 A VAILABLE | DL-4 3" Submersible, Electric, 130 gpm or up to 40' of head DL-1 2" Submersible, Electric, 30 gpm or up to 27' of head |
| Stancor Stainless Steel Pump | 10 A VAILABLE | •SSS-100, 2" Submersible, Electric, 100 gpm or up to 60' of head •SSS-75, 2" Submersible Electric, 80 gpm or up to 40' of head |
| Godwin Power Diesel Generator Sets | 1 AVAILABLE | • 26kW-R Series, Critically Silenced |
| Gasoline Generator Sets | 1 AVAILABLE | • 3000 Watt, Portable Honda Model |
| Godwin Portable Light Towers | 3 A VAILABLE | •GLT 416, 4000 Watts, Coverage of 5-7 acres |
| LWT Pit Hog Dredge | 1 AVAILABLE | • 40HP Electric Submersible Remote Control Dredge |
| Road Ramp Crossings | 10 A VAILABLE | •4", 6", 8" and 12" Road Ramps Crossings |
| Hydraulic Hoses | 800 FEET | • ¼", ½", ¾" and 1" Hydraulic Hose with Couplers |
| Heavy Duty Hoses | 8000 FEET | • 2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge Hose Available with Quick Disconnect Fittings |
| Bauer Light Weight, Quick Disconnect Pipe | 7200 FEET | • 4", 6", 8", and 12" Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths |
| Pump Accessories | 4000 IN STOCK | Bauer and Camlock Fittings from 2-12" Available |
| 18" HDPE Pipe | 2000 FEET | ● 18" DR 26 and 18" DR 32½ HDPE Pipe |
| Pump Parts | 900 IN STOCK | • Common Wear Parts for all Pumps Already in Stock |
| Cherne and Lansas Pipe Plugs | 31 AVAILABLE | • 4-8", 6", 8-12", 12-18", 12-24", 18-24", 15-30", 24-36" and 24-42", 35-48", 84" with Protective Sleeves and Poly-Lift Line Inflators |











The Pacific Pump and Power Team Dominick, Arlo, Hurley, Ana, Paul, Jill, Jonah, Mana