

The Pacific Pipeline





SEWER WORK ON UMI STREET AND RICHARD LANE!





Insituform Technologies did two Cured In Place Pipe (CIPP) shots one on August 18th and one on August 20th. Pacific Pump and Power was hired to bypass the sewer while this pipe rehabilitation was in progress. What seamed line a couple of low flow bypasses with just a 12" line over on Richard Lane and a 15" line on Umi St. turned out to be fairly large bypasses. The slope of the sewer caused very high velocities in the sewer system and therefore deceptively high sewer flows.





Pacific Pump and Power did the primary bypass on Richard Lane with two 8" Dri-Prime Diesel CD225M Godwin Pumps. To keep the noise level down for the residents Critically Silenced pumps were used. On Richard lane there were coupled laterals that had to be dealt with. One was a little 6" line that required a 4" CD100M Diesel Dri-Prime Godwin and one was a 15" which required two 6" CD150M Godwin Dri-Prime Diesel Critically Silenced Pumps. In order to achieve a quick set up time and tear down time since this bypass was only a day, Pacific Pump and Power used steel galvanized Bauer QD piping and road ramps.

On Umi St Pacific Pump and Power had to start our bypass on King St in the intersection of King St and Umi St. In order to avoid traffic delay on King St road ramps were used so the sewage could flow under the cars without having to dig up the road. This bypass required the use of three 8" Godwin Dri-Prime CD225M Critically Silenced diesel pumps. This provides a maximum bypass capacity of 13,392,000 Gallons per day! This bypass only had one small lateral that required a 4" Dri-Prime Godwin Pump.

Insituform had yet another successful project with the help of Pacific Pump and Power!



The Pacific Pipeline



The Monthly Newsletter of Pacific Pump and Power, Distributor of Godwin Pumps[®]

Rental • Sales • Service • Operations

September 2011

127 Pumps, Generators, Light Plants, Road Ramps and Dredges Available for Rent or Purchase in Hawaii

Pump Type	Quantity	Pump Model and Description
	Available	
Godwin Dri-Prime CD Series Pumps, High Volume, Medium Head, Large Solids-Handling Capabilities	42 A VAILABLE	 DPC300 12" Diesel, up to 5000 gpm or up to 115' of head DPC300 12" Electric, up to 4000 gpm or up to 115' of head CD225M 8" Diesel, up to 3100 gpm or up to 183' of head CD225M 8" Electric, up to 3100 gpm or up to 175' of head CD150M 6" Diesel, up to 1700 gpm or up to 160' of head CD103M 4" Diesel, up to 1000 gpm or up to 170' of head CD100M 4" Diesel, up to 750 gpm or up to 115' of head CD80M 3" Diesel, up to 450 gpm or up to 93' of head
Godwin HL Series, High Head Pumps with Solids-Handling Capabilities	6 AVAILABLE	 HL5M 6" Diesel, up to 1450 gpm or up to 500' of head HL80M, 3" Diesel, up to 450 gpm or up to 325' of head
Godwin Heidra Hydraulic Submersibles	4 A VAILABLE	 HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head HS100TD 4", Diesel, up to 800 gpm or up to 130' of head HS80-HH 3", Diesel, up to 420 gpm or up to 125' of head
Sub-Prime Elec tric Submersibles	29 AVAILABLE	 Godwin GSP600SV, 8", up to 3650 gpm or up to 82' of head Godwin GSP160HV, 6", up to 1200 gpm or up to 115' of head Godwin GSP55, 4", up to 550 gpm or up to 75' of head Toyo DL-4 3" Submersible, 130 gpm or up to 40' of head Toyo DL-1 2" Submersible, 30 gpm or up to 27' of head Stancor SSS-100, 2" Stainless, 100 gpm or up to 60' of head Stancor SSS-75, 2" Stainless, 80 gpm or up to 40' of head Stancor SV-100, 3" Stainless, 100 gpm or up to 50' of head Stancor SV-50, 2" Stainless, 80 gpm or up to 40' of head
Wet-Prime Gas Trash Pumps	11 AVAILABLE	 GTP80HX, 3" up to 355 gpm or up to 90' of head WT40X, 4" up to 430 gpm or up to 92' of head PTS4 4" up to 705 gpm or up to 106' of head QP4TH 4" up to 555 gpm or 92' of head
Versamatic Diaphragm Pumps	5 AVAILABLE	 Versamatic Air Operated E3, 3", up to 260 gpm Versamatic Air Operated E2, 2", up to 155 gpm
Godwin Power Diesel Generator Sets	1 AVAILABLE	• 26kW-R Series, Critically Silenced
Gasoline Generator Sets	1 AVAILABLE	• 3000 Watt, Portable Honda Model
Godwin Portable Light Towers	3 A VAILABLE	• GLT 416, 4000 Watts, Coverage of 5-7 acres
LWT Pit Hog Dredge	1 AVAILABLE	• 40HP Electric Submersible Remote Control Dredge
Road Ramp Crossings	10 A VAILABLE	• 4", 6", 8" and 12" Road Ramps Crossings
Air Compressor	1 Available	Ingersoll Rand 250 CFM air compressor with pneumatic hose reel
Hydraulic Hoses	800 FEET	• ¼", ½", ¾" and 1" Hydraulic Hose with Couplers
Heavy Duty Hoses	8000 FEET	• 2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge Hose Available with Quick Disconnect Fittings
Bauer Light Weight, Quick Disconnect Pipe	7200 FEET	• 4", 6", 8", and 12" Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths
Pump Accessories	4000 IN STOCK	Bauer and Camlock Fittings from 2-12" Available
HDPE Pipes and Fittings	2400 FEET	 18" DR 26 and 18" DR 32½ HDPE Pipe 12" DR11 HDPE Pipe 12", 14" 18", 24" HDPE Fittings
Pump Parts	900 IN STOCK	Common Wear Parts for all Pumps Already in Stock
Pipe Plugs	33 AVAILABLE	• 4-8", 6", 8-12", 12-18", 12-24", 18-24", 15-30", 24-36" and 24-42", 24-48", 84" with Protective Sleeves and Poly-Lift Line Inflators







The Pacific Pump and Power Team Paul, Arlo, Kristin, Rene'e, Mana, and Kamaka





