

The Pacific Pipeline

The Monthly Newsletter of Pacific Pump and Power Rental • Sales • Service • Operations

January 2013 License# C-32223

Rehabilitation on the Leeward Side

Jennings Pacific LLC is rehabilitating the main sewer transmission line from Lualualei pump station to the Waianae waste water treatment plant. They utilized two 8" CD225M Critically Silenced Dri-Prime pumps to bypass the pump stations flows while installing new valves and piping in the valve box outside the pump station.



Jennings is bypassing through 12" butt fused HDPE piping to ensure that there is no disruption to local residents. While this bypass line is active they will be installing a brand new 22" HDPE sewer line to replace the deteriorated line that is currently in place.

PPP is offering an HDPE Fusion Training Course in our Kapolei Yard March 11, 12, 13 - Sign up by February 15th!



The Small Diameter Operator Qualification session prepares students who work in small diameter applications (¼â€ CTS to 6†DIPS - 16mm to 180mm) to understand the theory of fusion and properly fuse small diameter pipe. Participants go hands-on with our smallest machines, the Mini-Mc® and 1LC, and learn saddle fusion techniques on the Sidewinder®. The course also covers some of McElroy's most popular machines such as the Pit Bull® 14, 2LC and Pit Bull® 26.

With McElroy University, students put theory and instruction into practice. Each Operator Qualification session is divided into approximately 30% classroom instruction and 70% hands-on application to provide better learning opportunities and real-world experience with McElroy equipment and pipe fusion processes.

After Operator Qualification training is complete, students undergo testing, both written and hands-on, to ensure they possess the skills and knowledge required in the field as defined by ASTM standard F2620 and PPI technical reports TR-33 and TR-41. Students who successfully pass the test receive a McElroy University Small Diameter Operator Qualification training certificate and wallet card. Certification lasts for 2 years and can be renewed with follow-up testing.

TUITION: \$950

This Session Covers:

- » Fusion Theory
- » Proper Fusion Techniques
- » Sidewall Fusion
- » Application Tips
- » Equipment Design
- » Troubleshooting Resources
- » DOT Requirements (PHMSA)
- » Preventative Maintenance
- » ASTM Standards

Sign up for March 11, 12, 13 @ our Campbell Location

SESSION LENGTH: 3 DAYS

Call today at 672-8198 or visit us at Campbell Industrial: 91-503 Nukuawa Street, Kapolei



The Pacific Pipeline

The Monthly Newsletter of Pacific Pump and Power

January 2013 License# C-32223

Rental • Sales • Service • Operations Quantity Pump Model and Description Pump Type Available Oahu Yard 45 AVAILABLE Godwin Dri-Prime CD Series Pumps, High • DPC300 12" Diesel, up to 5000 gpm or up to 115' of head Volume, Medium Head, • DPC300 12" Electric, up to 4000 gpm or up to 115' of head Large Solids-Handling Capabilities • CD225M 8" Diesel, up to 3100 gpm or up to 183' of head • CD225M 8" Electric, up to 3100 gpm or up to 175' of head • CD150M 6" Diesel, up to 1700 gpm or up to 160' of head • CD103M 4" Diesel, up to 1000 gpm or up to 170' of head • CD100M 4" Diesel, up to 750 gpm or up to 115' of head • CD80M 3" Diesel, up to 450 gpm or up to 93' of head Godwin HL Series, High Head Pumps with Solids-**5 AVAILABLE** • HL150M 6" Diesel, up to 1450 gpm or up to 500' of head **Handling Capabilities** • HL80M, 3" Diesel, up to 450 gpm or up to 325' of head Godwin Heidra Hydraulic Submersibles 6 AVAILABLE • HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head • HS150V 6", Diesel, up to 1600 gpm or up to 160' of head • HS100TD 4", Diesel, up to 800 gpm or up to 130' of head • HS80HH 3", Diesel, up to 420 gpm or up to 125' of head **Electric Submersibles** 21 AVAILABLE • Godwin GSP600SV, 8", up to 3650 gpm or up to 82' of head • Godwin GSP160HV, 6", up to 1200 gpm or up to 115' of head • Godwin GSP55, 4", up to 550 gpm or up to 75' of head • Toyo DL-4 3" Submersible, 130 gpm or up to 40' of head • Stancor SSS-100, 2" Stainless, 100 gpm or up to 60' of head • Stancor SSS-75, 2" Stainless, 80 gpm or up to 40' of head • Stancor SV-50, 2" Stainless, 80 gpm or up to 40' of head • Flygt Ready 8S, 2" Submersible, 80 gpm or up to 35' of head • Flygt 2740 SS sludge series 244HT, 210 gpm or up to 80' of head • Flygt 2740 SS drainage series B267 HT, 210 gpm or up to 150' of head 14 AVAILABLE • WT40X ,4"up to 430gpm or up to 92' of head Wet-Prime Gas Trash Pumps • Godwin GTP50HX 2" up to 185 gpm or up to 98' of head • Godwin GTP80HX, 3" up to 355gpm or up to 90' of head • Godwin GTP100HX, 4" up to 430 gpm or up to 92' of head • Multiquip QP4TH 4" up to 555 gpm or 92' of head Versamatic Diaphragm Pumps 5 AVAILABLE • Versamatic Air Operated E3, 3", up to 260 gpm • Versamatic Air Operated E2, 2", up to 155 gpm 1 AVAILABLE • 26kW-R Series, Critically Silenced Godwin Power Diesel Generator Sets **Gasoline Generator Sets** 2 AVAILABLE • 3000 Watt, Portable Honda Quiet Model • 2000 Watt, Portable Honda Quiet Model **Godwin Portable Light Towers** 3 AVAILABLE • GLT 416, 4000 Watts, Coverage of 5-7 acres LWT Pit Hog Dredge 1 AVAILABLE • 40HP Electric Submersible Remote Control Dredge 9 AVAILABLE **Road Ramp Crossings** • 4", 6", 8" and 12" Road Ramps Crossings 1 AVAILABLE Air Compressor • Ingersoll Rand 250 CFM air compressor with pneumatic hose reel Sewer Equipment Co. Jetter 1 AVAILABLE • 2000psi 60gpm, Portable Trailer Mounted Jetter **Hydraulic Hoses** 800 FEET • ¼", ½", ¾" and 1" Hydraulic Hose with Couplers **Heavy Duty Hoses** 8000 FEET • 2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge Hose Available with Quick Disconnect Fittings Bauer Light Weight, • 4", 6", 8", and 12" Bauer Light Weight Quick Disconnect Pipe 10000 FEET **Quick Disconnect Pipe** in 10' and 20' Lengths 4000 IN STOCK **Pump Accessories** • Bauer and Camlock Fittings from 2-12" Available **HDPE Pipes and Fittings** 2400 FEET • 18" DR 26 and 18" DR 32.5 HDPE Pipe • 12" DR11 HDPE Pipe • 12", 14" 18", 24" HDPE Fittings Pump Parts 1200 IN STOCK • Common Wear Parts for all Pumps Already in Stock Pipe Plugs 37 AVAILABLE • 4-8", 6", 8-12", 12-18", 18-24", 15-30", 24-36" and 24-42", 24-48", 84" with Protective Sleeves and Poly-Lift Line Inflators **McElroy Fusion Machines** 7 AVAILABLE • T500 II fuses 6-20" HDPE, T900 fuses 12-36" HDPE • PitBull 26 fuses 2-6" HDPE, 2LC fuses 1/2-2", Pitbull 14 fuses 1-4" 60 In STOCK **McElroy Parts** • Assorted parts and inserts Maui Yard Godwin Dri-Prime CD Series Pumps, High 1 AVAILABLE CD150M 6" Diesel, up to 1700 gpm or up to 160' of head Volume, Medium Head, Large Solids-Handling Capabilities 400 FEET • 6"Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths Bauer Light Weight, **Quick Disconnect Pipe** • 8" Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths **Heavy Duty Hoses** 40 FEET • 6" Heavy Duty Suction Hose Available with Quick Disconnect Fittings



Road Ramp Crossings

Gasoline Generator Sets



1

1 AVAILABLE



• 6" Road ramp crossing

• 2000 Watt, Portable Honda Quiet Model

